





寧波安牧國際貿易有限公司

NINGBO AMOL INTL. TRADE CO.,LTD.

Deep Groove Ball Bearing



Boundary dimensions(mm)				Basic load ratings(kN)		Limiting speeds(rpm)		Mass(Kg)	Bearing Number
d	D	B	r <sub>s min</sub>	C <sub>r</sub>	C <sub>or</sub>	Grease	Oil	(Approx.)	
10	26	8	0.3	4.55	1.96	29,000	34,000	0.019	6000
10	26	8	0.3	4.55	1.96	29,000	34,000	0.019	6000C3
12	28	8	0.3	5.10	2.39	26,000	30,000	0.021	6001
12	28	8	0.3	5.10	2.39	26,000	30,000	0.021	6001C3
15	32	9	0.3	5.60	2.83	22,000	26,000	0.03	6002
15	32	9	0.3	5.60	2.83	22,000	26,000	0.03	6002C3
17	35	10	0.3	6.80	3.35	20,000	24,000	0.039	6003
17	35	10	0.3	6.80	3.35	20,000	24,000	0.039	6003C3
20	42	12	0.6	9.40	5.05	18,000	21,000	0.069	6004
20	42	12	0.6	9.40	5.05	18,000	21,000	0.069	6004C3
25	47	12	0.6	10.1	5.85	15,000	18,000	0.08	6005
25	47	12	0.6	10.1	5.85	15,000	18,000	0.08	6005C3
30	55	13	1	13.2	8.3	13,000	15,000	0.116	6006
30	55	13	1	13.2	8.3	13,000	15,000	0.116	6006C3
35	62	14	1	16.0	10.3	12,000	14,000	0.155	6007
35	62	14	1	16.0	10.3	12,000	14,000	0.155	6007C3
40	68	15	1	16.8	11.5	10,000	12,000	0.19	6008
40	68	15	1	16.8	11.5	10,000	12,000	0.19	6008C3
45	75	16	1	21.0	15.1	9,200	11,000	0.237	6009
45	75	16	1	21.0	15.1	9,200	11,000	0.237	6009C3
50	80	16	1	21.8	16.6	8,400	9,800	0.261	6010
50	80	16	1	21.8	16.6	8,400	9,800	0.261	6010C3
55	90	18	1.1	28.3	21.2	7,700	9,000	0.388	6011
55	90	18	1.1	28.3	21.2	7,700	9,000	0.388	6011C3
60	95	18	1.1	29.5	23.2	7,000	8,300	0.414	6012
60	95	18	1.1	29.5	23.2	7,000	8,300	0.414	6012C3
65	100	18	1.1	30.5	25.2	6,500	7,700	0.421	6013




Boundary dimensions(mm)				Basic load ratings(kN)		Limiting speeds(rpm)		Mass(Kg)	Bearing Number
d	D	B	r <sub>s min</sub>	Cr	Cor	Grease	Oil	(Approx.)	
10	30	9	0.6	5.10	2.39	25,000	30,000	0.032	6200
10	30	9	0.6	5.10	2.39	25,000	30,000	0.032	6200C3
12	32	10	0.6	6.10	2.75	22,000	26,000	0.037	6201
12	32	10	0.6	6.10	2.75	22,000	26,000	0.037	6201C3
15	35	11	0.6	7.75	3.60	19,000	23,000	0.045	6202
15	35	11	0.6	7.75	3.60	19,000	23,000	0.045	6202C3
17	40	12	0.6	9.60	4.60	18,000	21,000	0.066	6203
17	40	12	0.6	9.60	4.60	18,000	21,000	0.066	6203C3
20	47	14	1	12.8	6.65	16,000	18,000	0.106	6204
20	47	14	1	12.8	6.65	16,000	18,000	0.106	6204C3
25	52	15	1	14.0	7.85	13,000	15,000	0.128	6205
25	52	15	1	14.0	7.85	13,000	15,000	0.128	6205C3
30	62	16	1	19.5	11.3	11,000	13,000	0.199	6206
30	62	16	1	19.5	11.3	11,000	13,000	0.199	6206C3
35	72	17	1.1	25.7	15.3	9,800	11,000	0.288	6207
35	72	17	1.1	25.7	15.3	9,800	11,000	0.288	6207C3
40	80	18	1.1	29.1	17.8	8,700	10,000	0.366	6208
40	80	18	1.1	29.1	17.8	8,700	10,000	0.366	6208C3
45	85	19	1.1	32.5	20.4	7,800	9,200	0.398	6209
45	85	19	1.1	32.5	20.4	7,800	9,200	0.398	6209C3
50	90	20	1.1	35.0	23.2	7,100	8,300	0.454	6210
50	90	20	1.1	35.0	23.2	7,100	8,300	0.454	6210C3
55	100	21	1.5	43.5	29.2	6,400	7,600	0.601	6211
55	100	21	1.5	43.5	29.2	6,400	7,600	0.601	6211C3
60	110	22	1.5	52.5	36.0	6,000	7,000	0.783	6212
60	110	22	1.5	52.5	36.0	6,000	7,000	0.783	6212C3
65	120	23	1.5	57.5	40.0	5,500	6,500	0.99	6213
65	120	23	1.5	57.5	40.0	5,500	6,500	0.99	6213C3




寧波安牧國際貿易有限公司

NINGBO AMOL INTL. TRADE CO.,LTD.


Deep Groove Ball Bearing



Boundary dimensions(mm)				Basic load ratings(kN)		Limiting speeds(rpm)		Mass(Kg)	Bearing Number
d	D	B	r <sub>s min</sub>	C <sub>r</sub>	C <sub>or</sub>	Grease	Oil	(Approx.)	
30	37	4	0.2	1.14	0.950	3,300	3,800	0.006	6706
30	37	4	0.2	1.14	0.950	3,300	3,800	0.006	6706C3
20	27	4	0.2	1.04	0.730	5,000	5,700	0.0045	6704C3
25	32	4	0.2	1.10	0.840	4,000	4,600	0.005	6705
25	32	4	0.2	1.10	0.840	4,000	4,600	0.005	6705C3
17	23	4	0.2	1.00	0.660	5,000	6,700	0.0025	6703
17	23	4	0.2	1.00	0.660	5,000	6,700	0.0025	6703C3
20	27	4	0.2	1.04	0.730	5,000	5,700	0.0045	6704
12	18	4	0.2	0.930	0.530	8,300	9,500	0.002	6701C3
15	21	4	0.2	0.940	0.585	6,600	7,600	0.0025	6702
15	21	4	0.2	0.940	0.585	6,600	7,600	0.0025	6702C3
10	15	3	0.1	1.01	0.555	36,000	42,000	0.0015	6700
10	15	3	0.1	1.01	0.555	36,000	42,000	0.0015	6700C3
12	18	4	0.2	0.930	0.530	8,300	9,500	0.002	6701
80	200	48	3	164	125	3,600	4,200	6.76	6416C3
75	190	45	3	138	99.0	3,800	4,500	5.72	6415
75	190	45	3	138	99.0	3,800	4,500	5.72	6415C3
80	200	48	3	164	125	3,600	4,200	6.76	6416
65	160	37	2.1	111	72.5	4,400	5,200	3.3	6413C3
70	180	42	3	128	89.5	4,100	4,800	4.83	6414
70	180	42	3	128	89.5	4,100	4,800	4.83	6414C3
60	150	35	2.1	102	64.5	4,800	5,700	2.77	6412
60	150	35	2.1	102	64.5	4,800	5,700	2.77	6412C3
65	160	37	2.1	111	72.5	4,400	5,200	3.3	6413
50	130	31	2.1	83.0	49.5	5,700	6,700	1.88	6410C3
55	140	33	2.1	89.0	54.0	5,200	6,100	2.29	6411
55	140	33	2.1	89.0	54.0	5,200	6,100	2.29	6411C3



Boundary dimensions(mm)				Basic load ratings(kN)		Limiting speeds(rpm)		Mass(Kg)	Bearing Number
d	D	B	r <sub>s min</sub>	C <sub>r</sub>	C <sub>or</sub>	Grease	Oil	(Approx.)	
160	220	28	2	87.0	96.0	2,800	3,300	2.61	6932C3
170	230	28	2	86.0	95.5	2,600	3,100	2.74	6934
170	230	28	2	86.0	95.5	2,600	3,100	2.74	6934C3
180	250	33	2	110	119	2,400	2,900	4.76	6936
180	250	33	2	110	119	2,400	2,900	4.76	6936C3
190	260	33	2	113	127	2,300	2,700	4.98	6938
190	260	33	2	113	127	2,300	2,700	4.98	6938C3
200	280	38	2.1	157	168	2,200	2,600	7.1	6940
200	280	38	2.1	157	168	2,200	2,600	7.1	6940C3
10	22	6	0.3	2.7	1.27	30,000	36,000	0.009	6900
10	22	6	0.3	2.7	1.27	30,000	36,000	0.009	6900C3
12	24	6	0.3	2.89	1.46	27,000	32,000	0.011	6901
12	24	6	0.3	2.89	1.46	27,000	32,000	0.011	6901C3
15	28	7	0.3	3.65	2.00	24,000	28,000	0.016	6902
15	28	7	0.3	3.65	2.00	24,000	28,000	0.016	6902C3
17	30	7	0.3	4.65	2.58	22,000	26,000	0.018	6903
17	30	7	0.3	4.65	2.58	22,000	26,000	0.018	6903C3
20	37	9	0.3	6.40	3.70	19,000	23,000	0.036	6904
20	37	9	0.3	6.40	3.70	19,000	23,000	0.036	6904C3
25	42	9	0.3	7.05	4.55	16,000	19,000	0.042	6905
25	42	9	0.3	7.05	4.55	16,000	19,000	0.042	6905C3
30	47	9	0.3	7.25	5.00	14,000	17,000	0.048	6906
30	47	9	0.3	7.25	5.00	14,000	17,000	0.048	6906C3
35	55	10	0.6	9.55	6.85	12,000	15,000	0.074	6907
35	55	10	0.6	9.55	6.85	12,000	15,000	0.074	6907C3
40	62	12	0.6	12.2	8.90	11,000	13,000	0.11	6908



Boundary dimensions(mm)				Basic load ratings(kN)		Limiting speeds(rpm)		Mass(Kg)	Bearing Number
d	D	B	r <sub>s min</sub>	C <sub>r</sub>	C <sub>or</sub>	Grease	Oil	(Approx.)	
12	28	7	0.3	5.10	2.39	26,000	30,000	0.019	16001
12	28	7	0.3	5.10	2.39	26,000	30,000	0.019	16001C3
180	280	31	2	117	134	2,300	2,700	6.49	16036C3
190	290	31	2	134	156	2,100	2,500	6.77	16038
190	290	31	2	134	156	2,100	2,500	6.77	16038C3
200	310	34	2	142	160	2,000	2,400	8.68	16040
200	310	34	2	142	160	2,000	2,400	8.68	16040C3
15	32	8	0.3	5.60	2.83	22,000	26,000	0.025	16002
15	32	8	0.3	5.60	2.83	22,000	26,000	0.025	16002C3
17	35	8	0.3	6.80	3.35	20,000	24,000	0.032	16003
17	35	8	0.3	6.80	3.35	20,000	24,000	0.032	16003C3
20	42	8	0.3	7.90	4.50	18,000	21,000	0.051	16004
20	42	8	0.3	7.90	4.50	18,000	21,000	0.051	16004C3
25	47	8	0.3	8.35	5.10	15,000	18,000	0.06	16005
25	47	8	0.3	8.35	5.10	15,000	18,000	0.06	16005C3
30	55	9	0.3	11.2	7.35	13,000	15,000	0.091	16006
30	55	9	0.3	11.2	7.35	13,000	15,000	0.091	16006C3
35	62	9	0.3	11.7	8.20	12,000	14,000	0.11	16007
35	62	9	0.3	11.7	8.20	12,000	14,000	0.11	16007C3
40	68	9	0.3	12.6	9.65	10,000	12,000	0.125	16008
40	68	9	0.3	12.6	9.65	10,000	12,000	0.125	16008C3
45	75	10	0.6	12.9	10.5	9,200	11,000	0.171	16009
45	75	10	0.6	12.9	10.5	9,200	11,000	0.171	16009C3
50	80	10	0.6	13.2	11.3	8,400	9,800	0.18	16010
50	80	10	0.6	13.2	11.3	8,400	9,800	0.18	16010C3