




寧波安牧國際貿易有限公司

NINGBO AMOL INTL. TRADE CO.,LTD.

Miniature Ball Bearing




Boundary dimensions(mm)				Basic load ratings(kN)		Limiting speeds(rpm)		Mass(g)	Bearing Number
d	D	B	r _{s min}	C _r	C _{or}	Grease	Oil	(Approx.)	
9	14	3	0.1	920	465	36,000	42,000	1.4	679
9	14	3	0.1	920	465	36,000	42,000	1.4	679C3
7	11	2.5	0.1	555	269	40,000	47,000	0.67	677C3
8	12	2.5	0.1	515	252	38,000	45,000	0.75	678
8	12	2.5	0.1	515	252	38,000	45,000	0.75	678C3
6	10	2.5	0.1	465	196	43,000	51,000	0.65	676
6	10	2.5	0.1	465	196	43,000	51,000	0.65	676C3
7	11	2.5	0.1	555	269	40,000	47,000	0.67	677
4	7	2	0.08	222	88.0	54,000	63,000	0.28	674C3
5	8	2	0.08	217	91.0	49,000	57,000	0.32	675
5	8	2	0.08	217	91.0	49,000	57,000	0.32	675C3
3	6	2	0.08	242	94.0	60,000	71,000	0.2	673
3	6	2	0.08	242	94.0	60,000	71,000	0.2	673C3
4	7	2	0.08	222	88.0	54,000	63,000	0.28	674
2.5	5	1.5	0.08	153	59.0	70,000	82,000	0.11	67/2.5
2.5	5	1.5	0.08	153	59.0	70,000	82,000	0.11	67/2.5C3
9	24	7	0.3	3,400	1,450	31,000	36,000	14	609
9	24	7	0.3	3,400	1,450	31,000	36,000	14	609C3
7	19	6	0.3	2,240	910	34,000	40,000	8	607C3
8	22	7	0.3	3,350	1,400	32,000	37,000	12	608
8	22	7	0.3	3,350	1,400	32,000	37,000	12	608C3
6	17	6	0.3	2,190	865	35,000	42,000	6	606
6	17	6	0.3	2,190	865	35,000	42,000	6	606C3
7	19	6	0.3	2,240	910	34,000	40,000	8	607
4	12	4	0.2	970	360	43,000	51,000	2.1	604C3
5	14	5	0.2	1,330	505	39,000	46,000	3.5	605
5	14	5	0.2	1,330	505	39,000	46,000	3.5	605C3



寧波安牧國際貿易有限公司

NINGBO AMOL INTL. TRADE CO.,LTD.

Miniature Ball Bearing



Boundary dimensions(mm)				Basic load ratings(kN)		Limiting speeds(rpm)		Mass(g)	Bearing Number
d	D	B	r _{s min}	C _r	C _{or}	Grease	Oil	(Approx.)	
1.5	4	1.2	0.15	102	29.0	88,000	100,000	0.07	68/1.5
1.5	4	1.2	0.15	102	29.0	88,000	100,000	0.07	68/1.5C3
2.5	6	1.8	0.08	209	73.0	65,000	76,000	0.22	68/2.5
2.5	6	1.8	0.08	209	73.0	65,000	76,000	0.22	68/2.5C3
1	3	1	0.05	80	22.0	120,000	140,000	0.05	681
1	3	1	0.05	80	22.0	120,000	140,000	0.05	681C3
2	5	1.5	0.08	171	51.0	74,000	87,000	0.13	682
2	5	1.5	0.08	171	51.0	74,000	87,000	0.13	682C3
3	7	2	0.1	390	130	58,000	68,000	0.33	683
3	7	2	0.1	390	130	58,000	68,000	0.33	683C3
4	9	2.5	0.15	640	224	49,000	57,000	0.67	684
4	9	2.5	0.15	640	224	49,000	57,000	0.67	684C3
5	11	3	0.15	715	282	43,000	51,000	1.1	685
5	11	3	0.15	715	282	43,000	51,000	1.1	685C3
6	13	3.5	0.15	1,080	440	39,000	46,000	1.9	686
6	13	3.5	0.15	1,080	440	39,000	46,000	1.9	686C3
7	14	3.5	0.15	1,170	505	37,000	44,000	2.1	687
9	20	6	0.3	2,480	1,090	32,000	38,000	8.2	699C3
8	19	6	0.3	1,990	865	33,000	39,000	7.3	698
8	19	6	0.3	1,990	865	33,000	39,000	7.3	698C3
9	20	6	0.3	2,480	1,090	32,000	38,000	8.2	699
6	15	5	0.2	1,350	530	37,000	44,000	3.8	696C3
7	17	5	0.3	1,610	715	35,000	41,000	5.2	697
7	17	5	0.3	1,610	715	35,000	41,000	5.2	697C3
5	13	4	0.2	1,080	430	40,000	47,000	2.4	695
5	13	4	0.2	1,080	430	40,000	47,000	2.4	695C3
6	15	5	0.2	1,350	530	37,000	44,000	3.8	696