





寧波安牧國際貿易有限公司

NINGBO AMOL INTL. TRADE CO.,LTD.

Taper Roller Bearing



Dimensions (mm)			Basic load ratings (kN)		Cone		Cup		Mass (Kg)	Bearing No.	
d	D	T	Cr	Cor	B	R	C	r	(Approx.)		ISO 355
17	40	13.25	20.5	20.3	12	1	11	1	0.08	30203	T2DB017
20	47	15.25	28.2	28.7	14	1	12	1	0.127	30204	T2DB020
30	72	20.75	48.5	51.5	19	1.5	14	1.5	0.398	31306	T7FB030
35	80	22.75	63.5	70.0	21	2	15	1.5	0.530	31307	T7FB035
40	90	25.25	77.0	85.5	23	2	17	1.5	0.738	31308	T7FB040
55	120	31.5	132	154	29	2.5	21	2	1.59	31311	T7FB055
65	140	36	173	204	33	3	23	2.5	2.42	31313	T7GB065
70	150	38	193	229	35	3	25	2.5	2.92	31314	T7GB070
75	160	40	215	256	37	3	26	2.5	3.47	31315	T7GB075
80	170	42.5	236	283	39	3	27	2.5	4.11	31316	T7GB080
85	180	44.5	247	293	41	4	28	3	4.85	31317	T7GB085
90	190	46.5	270	320	43	4	30	3	5.66	31318	T7GB090
95	200	49.5	296	355	45	4	32	3	6.47	31319	T7GB095
100	215	56.5	355	435	51	4	35	3	8.67	31320	T7GB100
22	44	15	27.0	31.5	15	0.6	11.5	0.6	0.106	320/22X	
28	52	16	33.0	40.5	16	1	12	1	0.146	320/28X	T4CC028
32	58	17	37.0	46.5	17	1	13	1	0.181	320/32X	T4CC032
20	42	15	24.9	27.9	15	0.6	12	0.6	0.097	32004X	T3CC020
25	47	15	27.8	33.5	15	0.6	11.5	0.6	0.114	32005X	T4CC025
30	55	17	37.5	46.0	17	1	13	1	0.166	32006X	T4CC030
35	62	18	41.5	52.5	18	1	14	1	0.224	32007X	T4CC035
40	68	19	50.0	65.5	19	1	14.5	1	0.273	32008X	T3CD040
45	75	20	57.5	76.5	20	1	15.5	1	0.346	32009X	T3CC045
50	80	20	62.5	88.0	20	1	15.5	1	0.366	32010X	T3CC050
45	85	24.75	82.0	100	23	1.5	19	1.5	0.607	32209	T3DC045
50	90	24.75	87.5	109	23	1.5	19	1.5	0.648	32210	T3DC050




Dimensions (mm)			Basic load ratings (kN)		Cone		Cup		Mass (Kg)	Bearing No.	
d	D	T	Cr	Cor	B	R	C	r	(Approx.)		ISO 355
55	120	45.5	215	275	43	2.5	35	2	2.44	32311	T2FD055
60	130	48.5	244	315	46	3	37	2.5	3.02	32312	T2FD060
65	140	51	273	350	48	3	39	2.5	3.66	32313	T2GD065
70	150	54	310	405	51	3	42	2.5	4.46	32314	T2GD070
75	160	58	355	470	55	3	45	2.5	5.35	32315	T2GD075
80	170	61.5	395	525	58	3	48	2.5	6.41	32316	T2GD080
85	180	63.5	405	525	60	4	49	3	7.15	32317	T2GD085
90	190	67.5	450	595	64	4	53	3	8.57	32318	T2GD090
95	200	71.5	505	670	67	4	55	3	10.1	32319	T2GD095
100	215	77.5	570	770	73	4	60	3	12.7	32320	T2GD100
55	80	17	44.5	73.5	17	1	14	1	0.274	32911	
60	85	17	51.0	83.0	17	1	14	1	0.296	32912	
65	90	17	48.5	85.0	17	1	14	1	0.315	32913	
70	100	20	68.5	110	20	1	16	1	0.487	32914	
75	105	20	69.5	114	20	1	16	1	0.511	32915	
80	110	20	72.0	121	20	1	16	1	0.54	32916	
85	120	23	94.0	157	23	1.5	18	1.5	0.773	32917	
90	125	23	97.5	168	23	1.5	18	1.5	0.817	32918	
95	130	23	101	178	23	1.5	18	1.5	0.851	32919	T2BC095
100	140	25	121	206	25	1.5	20	1.5	1.14	32920	
40	75	26	79.5	103	26	1.5	20.5	1.5	0.494	33108	T2CE040
45	80	26	84.5	115	26	1.5	20.5	1.5	0.542	33109	T3CE045
50	85	26	86.5	121	26	1.5	20	1.5	0.58	33110	T3CE050
55	95	30	111	155	30	1.5	23	1.5	0.846	33111	T3CE055
60	100	30	113	164	30	1.5	23	1.5	0.912	33112	T3CE060
65	110	34	144	211	34	1.5	26.5	1.5	1.28	33113	T3DE065




寧波安牧國際貿易有限公司

NINGBO AMOL INTL. TRADE CO.,LTD.

Taper Roller Bearing



Dimensions(mm)						Basic load ratings (kN)		Bearing No.	
Cone			Cup			T	Cr	Cor	
d	B	R	D	C	r				
			49.225	17.462	1.3				09196
			42.862	9.525	1.5				11520
15.875	14.288	1.5							11590
15.875	14.288	1.5	42.862	9.525	1.5	14.288	17.6	17.5	11590/20
22.225	20.168	1.5							1328
22.225	20.168	1.5							1380
22.225	20.168	1.5	52.388	14.288	1.5	19.368	40.5	43.0	1380/28
30.000	19.583	1.3	69.012	15.875	3.5	19.845	48.5	58.0	14117A/276
31.750	19.583	1.3							14125A
34.925	19.583	1.3							14137A
34.925	19.583	1.3	69.012	15.875	1.5	19.845	48.5	58.0	14137A/276
			69.012	15.875	1.3				14276
25.400	20.638	1.3							15100
25.400	20.638	1.3	62.000	14.288	3.5	19.050	46.5	54.0	15100/245
25.400	20.638	2							15101
25.400	20.638	2	61.912	14.288	0.8	19.050	46.5	54.0	15101/243
26.157	20.638	1.3							15103
26.157	20.638	1.3	62.000	14.288	0.8	19.050	46.5	54.0	15103/245
26.988	20.638	1.3							15106
26.988	20.638	1.3	62.000	14.288	0.8	19.050	46.5	54.0	15106/245
38.100	29.083	1.5							418
38.100	29.083	1.5	88.500	22.225	3.5	26.988	95.5	107	418/414
			133.350	26.195	3.5				47620
82.550	33.338	3.3							47686
82.550	33.338	3.3	133.350	26.195	3.5	33.338	153	235	47686/20
			139.992	28.575	3.5				572



Dimensions(mm)							Basic load ratings (kN)		Bearing No.
Cone			Cup			T	Cr	Cor	
d	B	R	D	C	r				
44.450	29.370	3.3	88.900	23.020	3.5	30.162	93.5	125	HM803149/10
			72.233	19.842	3.5				HM88610
35.717	25.400	3.3							HM88648
35.717	25.400	2.3	72.233	19.842	3.5	25.400	65.0	84.5	HM88648/10
34.925	25.400	2.3							HM88649
34.925	25.400	2.3	72.233	19.842	2.3	25.400	65.0	84.5	HM88649/10
			95.250	22.225	3.5				HM903210
44.450	28.575	0.8							HM903249
44.450	28.575	0.8	95.250	22.225	3.5	30.958	96.0	116	HM903249/10
			63.000	13.500					JL69310
38.000	17.000	1.3							JL69349
38.000	17.000	1.3	63.000	13.500		17.000	38.5	52.5	JL69349/10
			82.000	17.000	3				JLM104910
			145.000	27.000	3				JM718110
90.000	34.000	2.5							JM718149
90.000	34.000	2.5	145.000	27.000	3	35.000	189	279	JM718149/10
			50.292	10.668	3.5				L44610
25.400	14.732	1.3							L44643
25.400	14.732	1.3	50.292	10.668	1.3	14.224	28.8	34.0	L44643/10
26.988	14.732	1.3							L44649
26.988	14.732	1.3	50.292	10.668	3.5	14.224	28.8	34.0	L44649/10
			50.292	10.668	3.5				L45410
29.000	14.732	1.3							L45449
29.000	14.732	1.3	50.292	10.668	3.5	14.224	28.0	35.5	L45449/10
			59.974	11.938					L68111



寧波安牧國際貿易有限公司

NINGBO AMOL INTL. TRADE CO.,LTD.

Taper Roller Bearing

34.988	16.764	1.3							L68149
--------	--------	-----	--	--	--	--	--	--	--------