



寧波安牧國際貿易有限公司

NINGBO AMOL INTL. TRADE CO.,LTD.

Stainless Steel Bearing

Boundary dimensions(mm)				Basic load ratings(kN)		Limiting speeds(rpm)	Mass(Kg)	Bearing Number
d	D	B	r _{s min}	Cr	Cor	Oil	(Approx.)	
45	75	16	1	21.0	15.1	9,200	0.237	SS6009-ZZ
50	80	16	1	21.8	16.6	8,400	0.261	SS6010-ZZ
55	90	18	1.1	28.3	21.2	7,700	0.388	SS6011-ZZ
30	55	13	1	13.2	8.3	13,000	0.116	SS6006-ZZ
35	62	14	1	16.0	10.3	12,000	0.155	SS6007-ZZ
40	68	15	1	16.8	11.5	10,000	0.19	SS6008-ZZ
40	68	15	1	16.8	11.5	10,000	0.19	SS6008-ZZ
17	35	10	0.3	6.80	3.35	20,000	0.039	SS6003-ZZ
20	42	12	0.6	9.40	5.05	18,000	0.069	SS6004-ZZ
25	47	12	0.6	10.1	5.85	15,000	0.08	SS6005-ZZ
10	26	8	0.3	4.55	1.96	29,000	0.019	SS6000-ZZ
50	90	20	1.1	35.0	23.2	7,100	0.454	SS6210-2RS
55	100	21	1.5	43.5	29.2	6,400	0.601	SS6211-2RS
30	62	16	1	19.5	11.3	11,000	0.199	SS6206-2RS
35	72	17	1.1	25.7	15.3	9,800	0.288	SS6207-2RS
40	80	18	1.1	29.1	17.8	8,700	0.366	SS6208-2RS
17	40	12	0.6	9.60	4.60	18,000	0.066	SS6203-2RS
45	85	19	1.1	32.5	20.4	7,800	0.398	SS6209-2RS
50	90	20	1.1	35.0	23.2	7,100	0.454	SS6210-2RS
55	100	21	1.5	43.5	29.2	6,400	0.601	SS6211-2RS
30	62	16	1	19.5	11.3	11,000	0.199	SS6206-2RS
35	72	17	1.1	25.7	15.3	9,800	0.288	SS6207-2RS
35	72	17	1.1	25.7	15.3	9,800	0.288	SS6207-2RS
40	80	18	1.1	29.1	17.8	8,700	0.366	SS6208-2RS
17	40	12	0.6	9.60	4.60	18,000	0.066	SS6203-2RS
20	47	14	1	12.8	6.65	16,000	0.106	SS6204-2RS
25	52	15	1	14.0	7.85	13,000	0.128	SS6205-2RS
10	30	9	0.6	5.10	2.39	25,000	0.032	SS6200-2RS
12	32	10	0.6	6.10	2.75	22,000	0.037	SS6201-2RS
15	35	11	0.6	7.75	3.60	19,000	0.045	SS6202-2RS
45	75	16	1	21.0	15.1	9,200	0.237	SS6009-2RS
50	80	16	1	21.8	16.6	8,400	0.261	SS6010-2RS
55	90	18	1.1	28.3	21.2	7,700	0.388	SS6011-2RS



寧波安牧國際貿易有限公司

NINGBO AMOL INTL. TRADE CO.,LTD.

Stainless Steel Bearing

Boundary dimensions(mm)						Basic load ratings(kN)		Limiting speeds(rpm)		Mass(Kg)	Bearing Number
d	D	B	D1	C1	r _s min	Cr	Cor	Grease	Oil	(Approx.)	
5	14	5	16	1	0.2	1,330	505	39,000	46,000	3.9	SSF605-ZZ
6	17	6	19	1.2	0.3	2,190	865	35,000	42,000	6.5	SSF606-ZZ
8	22	7	25	1.50	0.3	3,350	1,400	32,000	37,000	13	SSF608-ZZ
8	16	5	18	1.1	0.2	1,610	715	35,000	41,000	3.5	SSF688-Z

Boundary dimensions(mm)								Mass(Kg)	Bearing Number
d		D		B		r _s min		(Approx.)	
in	mm	in	mm	in	mm	in	mm		
1-3/8	34.925	2-1/2	63.500	0.5626	14.29	0.031	0.80	106.00	SSR22-ZZ
1-1/2	38.100	2-5/8	66.675	0.5626	14.29	0.031	0.80	141.00	SSR24-ZZ
1/2	12.700	1-1/8	28.575	0.3126	7.94	0.016	0.40	18.00	SSR8-ZZ
1	25.400	2	50.800	0.5000	12.70	0.031	0.80	85.00	SSR16-ZZ
1-1/8	28.575	2-1/8	53.975	0.5000	12.70	0.031	0.80	90.00	SSR18-ZZ
1-1/4	31.750	2-1/4	57.150	0.5000	12.70	0.031	0.80	95.00	SSR20-ZZ
5/8	15.875	1-3/8	34.925	0.3437	8.73	0.031	0.80	37.00	SSR10-ZZ
3/4	19.050	1-5/8	41.275	0.4374	11.11	0.031	0.80	47.00	SSR12-ZZ
7/8	22.225	1-7/8	47.625	0.5000	12.70	0.031	0.80	71.00	SSR14-ZZ
1/2	12.700	1-1/8	28.575	0.2500	6.35	0.016	0.40	18.00	SSR8
1-3/8	34.925	2-1/2	63.500	0.4374	11.11	0.031	0.80	106.00	SSR22
1-1/2	38.100	2-5/8	66.675	0.4374	11.11	0.031	0.80	141.00	SSR24
3/8	9.525	7/8	22.225	0.2189	5.56	0.016	0.40	11.00	SSR6
1	25.400	2	50.800	0.3752	9.53	0.031	0.80	85.00	SSR16
1-1/8	28.575	2-1/8	53.975	0.3752	9.53	0.031	0.80	90.00	SSR18
1-1/4	31.750	2-1/4	57.150	0.3752	9.53	0.031	0.80	95.00	SSR20
5/8	15.875	1-3/8	34.925	0.2181	5.54	0.031	0.80	37.00	SSR10